

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 March 2005 (17.03.2005)

PCT

(10) International Publication Number
WO 2005/024484 A1

(51) International Patent Classification⁷: **G02B 6/46**

(21) International Application Number:
PCT/SE2004/001192

(22) International Filing Date: 13 August 2004 (13.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0302397-5 5 September 2003 (05.09.2003) SE

(71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET LM ERICSSON** (publ)
[SE/SE]; S-164 83 Stockholm (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **CAGENIUS, Torbjörn** [SE/SE]; Stackvägen 16B, S-191 34 Sollentuna (SE).
MICKELSSON, Hans [SE/SE]; Cedergrensvägen 25, S-126 36 Hägersten (SE).

(74) Agent: **SVENSSON, Lena**; Ericsson AB, Patent Unit Core Networks, Älvsjö, Box 1505, S-125 25 Älvsjö (SE).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD TO MINIMIZE EXCESS CABLE LENGTH



(57) Abstract: The present invention relates to method and arrangement to minimize excess fiber cable in large-scale point-to-point fiber installations, between equipment ODF, AE located in different equipment cabinets 1, 2. Each cabinet comprises at least one casing 4, 5, which casings are arranged to connect fiber cables with equipment in the cabinets via fan-out fiber cables 6, 7. The method comprises the following steps:- Attaching one end of a ribbon fiber cable 3 to a casing 4 that is adherent to a first equipment cabinet 1. - Routing of the ribbon fiber cable with a minimum excess length to a casing 5 adherent to a second equipment cabinet 2. - Cutting the other end of the ribbon fiber cable 3. - Attaching the cut end of the ribbon fiber cable 3 to the casing 5 adherent to the second equipment cabinet 2.

WO 2005/024484 A1

METHOD TO MINIMIZE EXCESS¹ CABLE LENGTH

TECHNICAL FIELD OF THE INVENTION

The present invention relates to methods and arrangements to minimize excess length of fiber cable between different equipment locations.

5

DESCRIPTION OF RELATED ART

A challenge for large-scale point-to-point Fiber-To-The-Home installations is the large amount of fibers to terminate and route to active equipment in a central office. In a future scenario with all-fiber access, i.e. fiber replaces the current copper access, thousands of fibers or more could be terminated at one side. At these large sites, the optical distribution could be placed at one floor, while the active equipment could be placed at a different floor. This further emphasizes the importance of a flexible and cost effective fiber management solution in the central office. In a typical installation of today the outside plant fiber cable entering the central office must be terminated in a joint closure where it is fusion spliced to an indoor cable that terminates in a network side optical distribution frame ODF. The ODF is used as the interface. In the optical distribution frame ODF each fiber is accessible and in a transmission system designed for metro or backbone transport typically two ODFs (one for the network side and one for the equipment side) are used in order to obtain a full flexibility for equipment to network reconfiguration. Finally a patch cable is used to connect the fiber to the active equipment. One solution for the patch cable frequently used today is a breakout cable, which basically consist of several pre-connectorized patch cables inside a common cable sheath. This common sheath is easily removed and thereby provides flexibility to access the individual patch cables at the same it eases handling. Excess fiber is

30

handled at the ODF, at cable ladders or at active equipment. Winding the excess fiber on reels placed inside the cabinets or outside in a separate cabinet next to e.g. the ODF cabinet usually does it. This can be done due to the
5 relatively low quantities of fiber in the transport network. Storage of excess fiber cables is a problem that is well known, see for example US patent 5,708,751. However, in a full scale FTTH access network the huge amount of fibers will need an improved way of handling excess fiber.

10

SUMMARY OF THE INVENTION

The present invention solves problems related to expensive logistics and handling to keep track on fixed length breakout cables and space needed for winding of excess fiber
15 between equipment in different equipment locations, such as cabinets.

The problems are solved by the invention by a method to couple together one end of a ribbon fiber cable to a first equipment cabinet. Then route the ribbon fiber cable without
20 excess length to a second cabinet and finally couple together the other end of the ribbon fiber cable to the second cabinet.

More in detail, the problems are solved by a method to minimize excess fiber cable in large-scale point-to-point
25 fiber installations between equipment located in different equipment cabinets. Each cabinet comprises at least one fan-out casing. The casings are arranged to connect the ribbon fiber cables with equipment in the cabinets via fan-out fiber cables. The method comprises the following steps:

30 - One end of the ribbon fiber cable is attached to a casing that is adherent to a first equipment cabinet.

- The ribbon fiber cable is routed with a minimum excess length to a casing adherent to a second equipment cabinet.
 - The other end of the ribbon fiber cable is cut close to the casing adherent to a second equipment cabinet.
- 5 - The cut end of the ribbon fiber cable is attached to the casing adherent to the second equipment cabinet.

An arrangement according to the invention comprises means for performing the above mentioned method steps.

10 A purpose with the invention is to eliminate fiber excess length when connecting equipment in separate equipment cabinets.

Yet another advantage is that the cost of logistics and handling of different pre-connectorized cables are eliminated.

15 The invention will now be described more in detail with the aid of preferred embodiments in connection with the enclosed drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Figure 1 shows a block schematic illustration of a ribbon fiber cable and fan-out cables attaching equipment in two equipment cabinets.

Figure 2 shows a fan-out casing which is used when fiber cables are spliced together.

25 Figure 3 shows in a flow-chart some essential steps of the invention.

DETAILED DESCRIPTION OF EMBODIMENTS

Figure 1 discloses two equipment cabinets, a first cabinet 1 and a second cabinet 2. The first cabinet 1 is in this example an optical distribution frame ODF cabinet and comprises passive equipment like ODFs having individual MU connectors 9. The second cabinet 2 is an active equipment cabinet with eight channel array transmitters. Two fibers per subscriber is used, one for up link and one for down link. The ODF is used as an interface between the optical fiber cable system represented by a line cable LC in figure 1, and active equipment AE in the second cabinet 2.

For a system similar to the one disclosed in the schematic figure 1, 480 ribbon cables with 8 fibers each are necessary to connect the active equipment cabinet with the ODF cabinet. On the ODF side an 8-f ribbon fan-out cable 6 to single MU fan-out casing 4 is used. The fan-out casing 4 can be handled as part of the cable and hangs inside the cabinet, sufficiently close to an ODF panel for the MU connectors to reach it. In the example disclosed in figure 1 however, the fan-out casing is placed in a snap-in holder on the inside of the ODF cabinet side-wall (as an alternative, it could be placed on the outside). 480 fan-out casings must be handled per 1920 subscriber cabinet. The fan-out casing 4 is arranged to connect the ribbon fiber cable 3 with the fan-out cable 6.

On the active equipment cabinet side a ribbon splice casing 5 is used to connect an MPO-8 connector 10 (with an 8-f ribbon) to the 8-f ribbon in the ribbon fiber cable 3 coming from the ODF cabinet. The casing 5 for the 8-f ribbon splice is assumed to be approximately the same size as the fan-out casing 4 and with similar properties, and thus to be handled in the same way.

The method according to the invention will now be explained.
The method comprises the following steps:

- 5 - One end of a ribbon fiber cable 3 is spliced to the fan-out fiber cable 6 via the fan-out casing 4. The fan-out casing is placed in a snap-in holder on the inside of the cabinet 1.
- The fan-out fiber cable 6 is attached, with a minimum of fan-out fiber cable excess length, to the optical distribution frame ODF in cabinet 1 via MU connectors 9.
- 10 - The ribbon fiber cable 3 is routed from cabinet 1 on a cable ladder system 11 with a minimum of excess to cabinet 2.
- The other end, i.e. the loose end, of the ribbon fiber cable is cut to a suitable length without cable excess
15 length between the two cabinets 1 and 2.
- The other end of a ribbon fiber cable 3 is spliced to a fan-out fiber cable 7 via the fan-out casing 5. The fan-out casing is placed in a snap-in holder on the inside of the cabinet 2.
- 20 - The fan-out fiber cable 7 is attached, with a minimum of fan-out fiber cable excess length, to the active equipment AE in cabinet 2 via a MPO-8 connector 10.

Figure 2 discloses the fan-out casing 5 more in detail. The
25 figure shows the fan-out cable 7 and the ribbon fiber cable 3 spliced together. The fan-out cable 7 is pre-connectorized with a MPO-8 connector 10. After estimation of suitable length of the ribbon fiber cable 3, without using excess length when routing the cable, the two cables 3 and 6 are
30 spliced together on a splicing sleeve 12. A shrinking tubing

13 is attached over the splicing sleeve 12 and the spliced fibers 3 and 6, as protection.

Figure 3 shows some of the most essential steps of the method in a flow chart. The flow chart is to be read
5 together with the earlier discussed figure 1 and 2. The most essential steps of the method are as follows:

- One end of the ribbon fiber cable 3 is attached to the fan-out fiber cable 6 via the fan-out casing 4. This is shown in figure 3 by a block 101.
- 10 - The fan-out fiber cable 6 is attached to the optical distribution frame ODF in cabinet 1 via MU connectors 9. This is shown in figure 3 by a block 102.
- The ribbon fiber cable 3 is routed from cabinet 1 on the cable ladder system 11 with a minimum of excess length to
15 cabinet 2. This is shown in figure 3 by a block 103.
- The other end of the ribbon fiber cable 3 is cut to a suitable length without cable excess length between the two cabinets 1 and 2. This is shown in figure 3 by a block 104.
- 20 - The other end of a ribbon fiber cable 3 is attached to the fan-out fiber cable 7 via the fan-out casing 5. This is shown in figure 3 by a block 105.
- The fan-out fiber cable 7 is attached to the active equipment AE in cabinet 2 via an MPO-8 connector 10. This
25 is shown in figure 3 by a block 106.

The arrangement used in the invention comprises means for adjusting the cables to suitable length without excess. As means for adjusting the cables, a fiber and cable cutter might be used. As means for assembling a connector, a fiber
30 cleaving tool, fiber polisher, assembly tool for connectors

might be used. The fusion splicing is preferably done with a portable fusion splice means.

As mentioned, the reciprocal order between the method steps is of minor importance for the invention. The equipment
5 locations can be located on different floors and routing of the ribbon fiber cable does not necessarily be on a cable ladder system. The splicing of cable ends does not necessarily have to be in a casing like the one disclosed in figure 2. The invention is of course not limited to the
10 above described and in the drawings shown embodiments but can be modified within the scope of the enclosed claims.

CLAIMS

1. Method to minimize excess fiber cable in large-scale point-to-point fiber installations, between equipment (ODF, AE) located in different equipment (1, 2),
5 characterized in that each location comprises at least one casing (4, 5), which casings are arranged to connect fiber cables with equipment in the locations via fan-out fiber cables (6, 7), which method comprises the following steps:
 - 10 - attaching one end of a ribbon fiber cable (3) to a casing (4) that is adherent to a first equipment location (1);
 - routing of the ribbon fiber cable with a minimum excess length to a casing (5) adherent to a second equipment location (2);
 - 15 - cutting the other end of the ribbon fiber cable (3);
 - attaching the cut end of the ribbon fiber cable (3) to the casing (5) adherent to the second equipment location (2).
2. Method to minimize excess fiber cable in large-scale
20 point-to-point fiber installations according to claim 1 whereby cables are attached by aid of fusion splicing.
3. Method to minimize excess fiber cable in large-scale point-to-point fiber installations according to claim 1
25 or 2 whereby the fan-out cables (6, 7) are routed between the casings (4, 5) and respective equipment (ODF, AE) without excess length.

4. Method to minimize excess fiber cable in large-scale point-to-point fiber installations according to any of claim 1-3 whereby fibers in the fiber cables (7, 3) are spliced together over a splicing sleeve (12).

5

5. Method to minimize excess fiber cable in large-scale point-to-point fiber installations according to any of claims 1-4 whereby a shrinking tubing (13) is attached over the splicing sleeve, as protection.

10

6. Arrangement to minimize excess fiber cable in large-scale point-to-point fiber installations, between equipment (ODF, AE) located in different equipment locations (1, 2), characterized in that each location comprises at least one casing (4, 5), which casings are arranged to connect fiber cables with equipment in the locations via fan-out fiber cables (6, 7), which arrangement comprises:

- 15
- means for attaching one end of a ribbon fiber cable (3) to a casing (4) that is adherent to a first equipment location (1);
 - 20
 - means for routing of the ribbon fiber cable with a minimum excess length to a casing (5) adherent to a second equipment location (2);
 - 25
 - means for cutting the other end of the ribbon fiber cable (3);
 - means for attaching the cut end of the ribbon fiber cable (3) to the casing (5) adherent to the second equipment location (2).

1/3




Fig. 1

2/3




Fig. 2

3/3




Fig. 3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 2004/001192

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: G02B 6/46

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: G02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5971623 A (MICHAEL F. WANAMAKER), 26 October 1999 (26.10.1999), abstract --	1-6
A	US 5659655 A (JOHN C. PILATOS), 19 August 1997 (19.08.1997), abstract --	1-6
A	US 5611017 A (NICHOLAS A. LEE ET AL), 11 March 1997 (11.03.1997), abstract --	1-6
A	US 5708751 A (MICHAEL MATTEI), 13 January 1998 (13.01.1998), abstract -- -----	1-6

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

18 November 2004

Date of mailing of the international search report

06-12-2004

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Lars Jakobsson/Els

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

30/10/2004

International application No.
PCT/SE 2004/001192

US	5971623	A	26/10/1999	AU	2927997 A	19/11/1997
				WO	9741476 A	06/11/1997
US	5659655	A	19/08/1997	AU	2927397 A	19/11/1997
				WO	9741475 A	06/11/1997
US	5611017	A	11/03/1997	CA	2222159 A	05/12/1996
				CN	1190469 A	12/08/1998
				DE	69614382 D,T	23/05/2002
				EP	0829028 A,B	18/03/1998
				SE	0829028 T3	
				EP	0978744 A	09/02/2000
				JP	11506546 T	08/06/1999
				US	5574817 A	12/11/1996
				WO	9638751 A	05/12/1996
US	5708751	A	13/01/1998	NONE		